

**AMENDMENTS TO THE CLAIMS**

Please amend the claims as follows:

1. (Previously Presented) A method for detecting oscillation in a repeater system comprising:

processing communication signals with a wireless communication device circuit embedded in a repeater; and

using the communication signals processed at the wireless communication device circuit to determine if the repeater system is in oscillation by attempting to establish a call from the wireless communication device circuit to a base station, and determining oscillation if the call cannot be established.

2. (Canceled)

3. (Original) The method of claim 1, wherein using the wireless communication device circuit comprises:

using the wireless communication device circuit to measure signal quality from the base station; and

determining oscillation if the signal quality meets a certain criteria.

4. (Original) The method of claim 3, wherein determining oscillation comprises determining oscillation if the signal quality degrades below a certain level.

5. (Original) The method of claim 3, wherein determining oscillation comprises determining oscillation if the signal quality degrades from a level that existed before the repeater was used.
6. (Original) The method of claim 3, wherein using the wireless communication device circuit comprises:
- obtaining signal to noise ratio value to measure the signal quality.
7. (Original) The method of claim 1, wherein using the wireless communication device circuit comprises:
- using the wireless communication device circuit to estimate at least one open loop power control parameter;
- establishing a communication link from the wireless communication device circuit to a base station using the estimated open loop power control parameter;
- receiving at least one closed loop power control command from the base station; and
- determining oscillation if the closed loop power control command is greater than a certain amount.
8. (Original) The method of claim 7, wherein using the wireless communication device circuit comprises estimating at least a required transmit power to complete the call, wherein receiving closed loop power control commands comprises receiving at least power adjustment

information, and wherein determining oscillation comprises determining oscillation if the power adjustment information is greater than a certain amount.

9. (Original) The method of claim 1, further comprising:

reducing gain of repeater if the repeater system is in oscillation.

10. (Previously Presented) Apparatus for detecting oscillation in a repeater system comprising:

a wireless communication device circuit embedded in a repeater, wherein the wireless communication device circuit is configured to process communication signals;

means for using the communication signals processed at the wireless communication device circuit to determine if the repeater system is in oscillation;

means for establishing a call from the wireless communication device circuit to a base station; and

means for determining oscillation if the call cannot be established.

11. (Canceled)

12. (Original) The apparatus of claim 10, wherein means for using the wireless communication device circuit comprises:

means for using the wireless communication device circuit to measure signal quality from the base station; and

means for determining oscillation if the signal quality meets a certain criteria.

13. (Previously Presented) The apparatus of claim 12, wherein the means for determining oscillation based on signal quality is configured to determine oscillation if the signal quality degrades below a certain level.

14. (Previously Presented) The apparatus of claim 12, wherein the means for determining oscillation based on signal quality is configured to determine oscillation if the signal quality degrades from a level that existed before the repeater was used.

15. (Original) The apparatus of claim 12, wherein means for using the wireless communication device circuit comprises:

means for obtaining signal to noise ratio value to measure the signal quality.

16. (Original) The apparatus of claim 10, wherein means for using the wireless communication device circuit comprises:

means for using the wireless communication device circuit to estimate at least one open loop power control parameter;

means for establishing a communication link from the wireless communication device circuit to a base station using the estimated open loop power control parameter;

means for receiving at least one closed loop power control command from the base station; and

means for determining oscillation if the closed loop power control command is greater than a certain amount.

17. (Previously Presented) The apparatus of claim 16, wherein means for using the wireless communication device circuit is configured to estimate at least a required transmit power to complete the call, wherein means for receiving closed loop power control commands comprises means for receiving at least power adjustment information, and wherein the means for determining oscillation based on the closed loop power control command is configured to determine oscillation if the power adjustment information is greater than a certain amount.

18. (Original) The apparatus of claim 10, further comprising:  
means for reducing gain of repeater if the repeater system is in oscillation.

19. (Previously Presented) An apparatus for detecting oscillation in a repeater system comprising:

a wireless communication device (WCD) configured to detect if the repeater system is in oscillation based on an attempt to establish a call to a base station, wherein oscillation is detected if the call cannot be established; and

a processor coupled to the WCD, configured to reduce the gain of the repeater system if the repeater system is in oscillation.

20. (Previously Presented) The method of claim 1, wherein the using step uses the ratio of energy of a chip of a pilot signal to total interference ( $E_c/I_o$ ) obtained from the processed communication signals to determine if the repeater system is in oscillation.

21. (Previously Presented) The method of claim 1, wherein the call is initiated at the wireless communication device circuit.

22. (Previously Presented) A machine-readable storage medium having instructions encoded thereon, which, when executed by a machine that is configured to read the encoded instructions from the machine-readable medium, cause the machine to perform operations, the instructions comprising:

program code to process communication signals with a wireless communication device circuit embedded in a repeater;

program code to attempt to establish a call from the wireless communication device circuit to a base station; and

program code to determine oscillation if the call cannot be established.

23. – 40. (Cancelled)